

Phone: 941-757-3696 Info@wfhinspect.com www.wfhinspect.com

Wind Mitigation Inspection

Village Brooke

3213-3217 Beneva Rd Sarasota FL, 34232

07/14/2023



Note to Policyholder:

Questions regarding the results of this inspection should be directed to a member of our Quality Assurance team by dialing the number listed above, or by simply emailing us at <u>info@wfhinspect.com</u>

Questions regarding the impact of this inspection and your insurance coverage or premiums should be directed to either your trusted insurance agent or your insurance carrier.

Limitation of Liability: West Florida Home Inspections, LLC inspections are purely observational in nature and based upon the accessible areas of the structure as well as any available documentation provided to the inspector during the time of inspection. West Florida Home Inspections, LLC is solely verifying the presence or lack thereof of mitigation features associated with the form, and makes no warranty, express or implied, regarding the suitability or condition of the structure under any circumstances.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 07/14/2023								
Owner Information								
Owner Name: Village Brooke Contact Person:								
Address: 3213-3217 Beneva Rd		Home Phone:						
City: Sarasota	Zip:	34232	Work Phone:					
County: Sarasota			Cell Phone: (941) 922-0141					
Insurance Company: Policy #:								
Year of Home: 1978	# of Stories: 2		Email: villagebrooke1@gmail.com					

NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.

- 1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?
 - A. Built in compliance with the FBC: Year Built <u>1978</u>. For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY) /////
 - B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built . For homes built in 1994, 1995, and 1996 provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY) ////
 - C. Unknown or does not meet the requirements of Answer "A" or "B"
- 2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.

2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
1. Asphalt/Fiberglass Shingle	//			
2. Concrete/Clay Tile	//			
3. Metal	6/11/2008	08 820236 00		
4. Built Up	/			
5. Membrane	6/11/2008	08 820236 00		
6. Other	/			

- A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.
 - B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.
 - C. One or more roof coverings do not meet the requirements of Answer "A" or "B".
 - D. No roof coverings meet the requirements of Answer "A" or "B".
- 3. Roof Deck Attachment: What is the weakest form of roof deck attachment?

A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.

B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.

C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent Sarasota

Inspectors Initials TG Property Address 3213-3217 Beneva Rd

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4

In	spec	ors Initials TG Property Address 3213-3217 Beneva Rd Sarasota
6.		 ondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined.
		C. Other Roof Any roof that does not qualify as either (A) or (B) above. sq ft; Total roof areasq ft
		B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of
		A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: feet
5.		<u>f Geometry</u> : What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of nost structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
		H. No attic access
		G. Unknown or unidentified
		E. Structural Anchor bolts structurally connected or reinforced concrete roof.F. Other:
		Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
		 D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
		minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
		C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a
		Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
		Metal connectors that do not wrap over the top of the truss/rafter, or
		corrosion. B. Clips
		Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ¹ / ₂ " gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe
	Mi	imal conditions to qualify for categories B, C, or D. All visible metal connectors are: Secured to truss/rafter with a minimum of three (3) nails, and
		Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
		Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
4.		<u>f to Wall Attachment</u> : What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within et of the inside or outside corner of the roof in determination of WEAKEST type) A. Toe Nails
4		G. No attic access.
		F. Unknown or unidentified.
		E. Other:
		or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf. D. Reinforced Concrete Roof Deck.

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Ispects and West Florida Home Inspections LLC | 239-896-3986 | 941-757-3696 | Info@Ispects.me

Opening Protection: What is the <u>weakest</u> form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart			Glazed Openings					
openi form (an "X" in each row to identify all forms of protection in use for each ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	Not Applicable- there are no openings of this type on the structure		\sim	\times	\times		X	
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
N	Opening Protection products that appear to be A or B but are not verified							
IN	Other protective coverings that cannot be identified as A, B, or C							
х	No Windborne Debris Protection	\times				\times		

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above

A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above

B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):

- ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
- SSTD 12 (Large Missile 4 lb. to 8 lb.)
- For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)

B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist

B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

<u>C.</u>	Exterior	Opening	Protection-	Wood	Structural	Panels	meeting	FBC	2007	All	Glazed	openings	are	covered	with
ply	wood/OS	B meeting	the requireme	nts of T	Table 1609.1	.2 of the	FBC 2007	7 (Lev	el C in	the	table abc	ove).			

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials TG Property Address 3213-3217 Beneva Rd Sarasota	
--	--

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 3 of 4

Ispects and West Florida Home Inspections LLC | 239-896-3986 | 941-757-3696 | Info@Ispects.me

C	N. Exterior Opening Protection (unverified shutter syste protective coverings not meeting the requirements of Answe with no documentation of compliance (Level N in the table	er "A", "B", or C" or sys						
	N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist							
		N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the						
	N.3 One or More Non-Glazed openings is classified as Level X	in the table above						
	X. None or Some Glazed Openings One or more Glazed openings		evel X in the table above.					
	MITIGATION INSPECTIONS MUST BE C Section 627.711(2), Florida Statutes, provides	~						
	Sta Sta	ense Type: tte Licensed Home Inspector						
Insp	West Florida Home Inspections		(941) 757-3696					
Qı	Qualified Inspector – I hold an active license as a: (c	heck one)						
0		ho has completed the statute						
	Building code inspector certified under Section 468.607, Florida Stat	tutes.						
	General, building or residential contractor licensed under Section 489	9.111, Florida Statutes.						
	Professional engineer licensed under Section 471.015, Florida Statute	es.						
Ц	Professional architect licensed under Section 481.213, Florida Statute							
Ш	Any other individual or entity recognized by the insurer as possessing verification form pursuant to Section 627.711(2), Florida Statutes.	g the necessary qualification	ns to properly complete a uniform mitigation					
	ndividuals other than licensed contractors licensed under Sec							
	nder Section 471.015, Florida Statutes, must inspect the struc							
	<u>Licensees under s.471.015 or s.489.111 may authorize a direct of</u> xperience to conduct a mitigation verification inspection.	employee who possesses	s the requisite skill, knowledge, and					
<u>сл</u>	Trenn Cachring	T	A					
1, _	, <u>IFONN GOENTING</u> am a qualified inspector and (print name)	i personally performed	the inspection of (ucensea					
CON	ontractors and professional engineers only) I had my employee	e () perform the inspection f inspector)					
an	and I agree to be responsible for his/her work.							
Qualified Inspector Signature: Date: 07/14/2023								
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally performed the inspection.								
res	Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that proof of identification was provided to me or my Authorized Representative.							
Sig	Signature: Date	e:07/14/20	23					
obt	An individual or entity who knowingly provides or utters a fals btain or receive a discount on an insurance premium to which f the first degree. (Section 627.711(7), Florida Statutes)							
	The definitions on this form are for inspection purposes only a s offering protection from hurricanes.	nd cannot be used to ce	rtify any product or construction feature					
Ins	nspectors Initials TG Property Address 3213-3217 Bene	eva Rd	Sarasota					
*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or								
	naccuracies found on the form. JIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155		Page 4 of 4					

Ispects and West Florida Home Inspections LLC | 239-896-3986 | 941-757-3696 | Info@Ispects.me



Front Elevation

Address



Left Elevation



Right Elevation



Rear Elevation



Rear Elevation



Roof Covering



corrugated concrete deck form



Structural





100% reinforced masonry



Unverified/Unrated Protection



Unverified/Unrated Protection



Roof covering Ispects and West Florida Home Inspections LLC | 239-896-3986 | 941-757-3696 | Info@Ispects.me

Roof geometry